FCamToGo™ Specification Sheet

CIJJRIX

version 1.2 issued 04-DEC-2019



CXFCAM2G-04	
Voltage	230Vac 50Hz
Power	120W
Operating Temperature	+5°C to +40°C
Working Humidity	<90%
LAN/Ethernet	4 ports PoE for FCam cameras
	4 ports local ethernet (2 in use)
	(can be extended with additional down-
	stream switches)
Power Input	UK type-G mains plug (others on request)
Alarm interface	4 x volt-free changeover relay contacts
	4 x opto-isolated voltage applied inputs
Status Screen	LCD (on Controller)
Dimensions	
Width	600mm
Depth	550mm

СЕ ГС 🖉 конз

About FCamController

The FCamToGo is a fast-install packaged solution which is pre-assembled and configured to your site requirements, saving large amounts of installer time fixing items to walls or building rack cabinets on site.

The standard FCamToGo CXFCAM2G-04 **includes** one FCam Controller, one Ciqurix I/O module, a Gigabit ethernet PoE switch, a quality British-made rack enclosure, and all associated power supplies to support 4 Ciqurix FCams in a stand-alone system with no additonal kit required. Just add up to 4 FCam cameras of your choice, PoE splitters, brackets, your choice of NVR, and of course cabling to the cameras. Up to 128 FCam cameras can be supported by extending the IP network and fitting additional distributed network switches around the site.

We also provide bespoke FCamToGo systems incorporating other items as the client's needs dictate; for example additional PoE ports, router, etc. Please contact us for details.